


Electric tacker J-165 Panel



- The extremely low-recoil panelling tacker is also suitable for fastening standard panelling clips.
 - Takes narrow crown staples of 15 to 26 mm and nails up to 25 mm
 - Easily visible staple level
- Extra-fine nozzle allows for precise work in hard-to-reach places and direct mounting of tongue-and-groove boards into the side of the groove.
 - Snap lock provides easy access for rapid troubleshooting
 - Correct impact force for soft or hard wood
 - Immediately ready for use after pushing back the trigger catch

Article number	031-0324
EAN Code	4009729011799
Loading capacity	110 x Nail E model J 125 x Narrow crown staple C model 4
processable materials	Tongue-and-groove boards / panelling with clips for walls and ceiling Tongue-and-groove boards / panelling without clips, attached directly Hardboard (2-6 mm) Mineral fibreboard (4-10 mm) Plywood (4-10 mm) Decorative moulding / corner mouldings
Features	staple inspection window Multistroke function Impact power adjuster Nozzle Tigger catch Express fault-clearance panel clip guide Integrated staple slider
Cable length in m	3,5
Pulse repetition rate	20 shots/min
line voltage	220 V / 50 H
Compliance	GS Intertek



Electric tacker J-165 Panel



Guarantees the right impact power for every job, no matter whether you're fastening into hard or soft wood.



The tacker's narrow and long nozzle also permits precision stapling at poorly accessible places.



Tacker is only ready for use after pushing back the trigger catch.